

**ED\_0005450neDrive\_00008541**


# EPAct Program

## Fuel Matrix Design Options


August 2, 2007

# Fuel Matrix No.1A

## (4 variable, mixed level (3x3x3x2))



- Computer generated optimal design
- 30 fuels
  - 21 fuels in 4-parameter matrix
    - G-Efficiency: 87.7%
  - Additional 2 E10s
  - 5 additional fuels to assess aromatics impact
  - 2 E85 fuels



### Fuel Matrix Design


Fuel Variables	#of Levels	Term in Model
T50	3	Main effects
T50 <sup>2</sup> , T90 <sup>2</sup> ,	3	
E10 <sup>2</sup> ,	3	
T50E10	3	
T90E10	3	
RVP	2	RVP E10

# **Ex. 5 - Deliberative/Ex. 4 CBI**

# **Ex. 5 - Deliberative/Ex. 4 CBI**


# Fuel Matrix No.1C

(4 variable, mixed level (3x3x3x2))



- Computer generated optimal design
- 27 fuels
- G-Efficiency\*: 72.5%

\* >60% considered satisfactory



## Fuel Matrix Design


Fuel Variables	#of Levels	Tests in Matrix
T50	3	T50 <sup>2</sup> , T90 <sup>2</sup> , EOH <sup>2</sup>
T90	3	T50 <sup>2</sup> EOH, T90 <sup>2</sup> EOH
EOH	3	T50EOH, T90EOH, RPEOH
RPEOH	2	

## **Ex. 5 - Deliberative/Ex. 4 CBI**

# **Ex. 5 - Deliberative/Ex. 4 CBI**


# Fuel Matrix No.1D

(4 variable, mixed level (3x3x3x2))



- Computer generated optimal design
- 26 fuels
- G-Efficiency\*: 69.6%

\* >60% considered satisfactory



## Fuel Matrix Design

Fuel Variables	#of Levels	Tests in Matrix
T50	3	T50 <sup>2</sup> , T90 <sup>2</sup> , EOH <sup>2</sup>
T90	3	T50EOH, T90EOH
EOH	3	
RVP	2	RPEOH

## **Ex. 5 - Deliberative/Ex. 4 CBI**

# **Ex. 5 - Deliberative/Ex. 4 CBI**